

Service Instruction

No. 27

Date: May 15, 1987

Subject: Radio Filter P/N NOR 7.385-12

Description:

This Service Instruction supplies informations in the replacement of the radio filter P/N NOR 7.385-1 with the new one identified by P/N NOR 7.385-12.


Applicable on: P 68 serie

Weight and balance change: //

Publications attached: Parts Catalog

Instructions:

- 1) To enter to radio filter P/N NOR 7.385-1, remove interior cabin panel P/N 68-8.2021-1;
- 2) Identify all connections to the installed radio filter;
- 3) Remove old radio filter P/N NOR 7.385-1;
- 4) Install a new radio filter P/N NOR 7.385-12;
- 5) With reference to the following wiring diagram, connect new radio filter;



FEMALE
front view

1	-----	N.C.
2	-----	+28 V. ADF IN (to bkr)
3	-----	+28 V. ADF OUT (to equip.)
4	----awg 16-----	+28 V. COM 1 IN
5	----awg 16-----	+28 V. COM 1 OUT
6	-----	+28 V. NAV 1 IN
7	-----	+28 V. NAV 1 OUT
8	----awg 16-----	+28 V. COM 2 IN
9	----awg 16-----	+28 V.COM 2 OUT
10	-----	+28 V. NAV 2 IN
11	-----	+28 V. NAV 2 OUT
12	-----	-28 V. GND

- 6) Secure electrical wires;
- 7) Check radio systems (VHF & ADF);
- 8) Reinstall interior cabin panel.

KIT NUMBER: 68-041